



ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MORE

Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 702414, TU® Steel-Backed PTFE Lined Thrust Washers - METRIC

Isostatic TU® Thrust Washer Bearings

- Standard stock products
- Self-lubricating dry sliding bearing
- A steel-backed composite material comprised of:
 - Low carbon steel backing for extremely high load capacity-.50 – 2.7mm thick
 - Sintered bronze offers optimal heat dispersion –.20 - .35 mm thickness and
 - PTFE – lead sliding surface creates a low friction coefficient and allows for a wide temperature range – thickness .2 mm
- Can be used where many liquid lubricants fail; also performs well with



[+ more](#)

[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

48 MM I.D. x 74 MM O.D. x 2.0 MM Length, TU, Steel Back, PTFE & Pb Lined Composite, Thrust Washer Bearing, Metric

Specifications

Catalog Number	WM45TU
Interchange #	PAW 48 P10 WC45DU
Unit of Measure	Each
Material	Steel-Backed PTFE Lined
Material Standard	Steel-Backed PTFE Lined

Avg Unit Weight	0.0796 lb
UPC Code	00846802071530

Dimensions

Nominal Inner Diameter	48 mm
Nominal Outer Diameter	74 mm
Nominal Thrust Washer Thickness	2 mm
Nominal Dowel Hole Diameter	4 mm
Nominal Dowel Hole Pitch Circle Diameter	61 mm
Nominal Housing Recess Depth	1.5 mm

Tolerances

Inner Diameter Tolerance	+ .25 mm
Outside Diameter Tolerance	- .25 mm
Thrust Washer Thickness Tolerance	+ .05 mm
Dowel Hole Diameter Tolerance	+ .25 mm
Dowel Hole Pitch Circle Diameter Tolerance	- .24 mm
Housing Recess Depth Tolerance	+ .25 mm

Performance Data

Load - P Max Value	36,250 lb/in ²
Speed - V Max Value	1,900 ft ² /min
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	102,000